

T5 LongLast™ - High Efficiency, G5 Cap





FT5/14W/865/GE/LL/SL1/30
61088

Product information

T5 LongLast™ lamps are triphosphor fluorescent lamps with 16mm outer diameter (5/8 of an inch). These lamps feature “Starcoat™ Technology” that delivers high quality triphosphor performance. GE produces two ranges of T5 LongLast™ lamps in 4 different lengths:

- High Efficiency offering high lumens per watt
- High Output offering improved lumen package

Application areas

- | | |
|---|--|
|  Retail |  Office |
|  Education |  Industrial |



Product data

Product Code	61088
Bulb Shape	Tubular
Bulb Diameter [mm]	16
Bulb maximum overall diameter [mm]	16
Cap to Cap Length (Max) [mm]	549
Net weight per piece [g]	52
Gross weight per piece [g]	68
Mercury Content [mg]	2.5
UV radiance	Exempt
Brand	GE Lighting
Cap/Base	G5

Performance data

Colour Code	865
Rated Lumens [lm]	1250
Lumen at 25°C [lm]	1140
Weighted energy consumption [kWh/1000h]	15.4
Rated efficacy [lm/W]	91
Energy efficiency class (EEC)	A+
Rated Life [h]	30000
Rated median life on electronic (HF / ECG) ballast on IEC 12-hour cycle	36000
Rated median life on electronic (HF / ECG) ballast on IEC 3-hour cycle	30000
Nominal correlated colour temperature (CCT) [K]	6400
Nominal lumens [lm]	1250
Colour Rendering Index (CRI) [Ra]	85



Electrical data

Rated power [W]	14.0
Design Ambient Temperature [°C]	35
Design Lamp ambient temperature [°C]	35
Starting ambient temperature range	-15
Dimming Capability	Yes
Nominal power [W]	14.0


Logistic data

DUN Code	10043168610886
EAN Code	0043168902441
Pack Quantity	30
Inner pack type	SLEEVE
Outer pack type	OUTER BOX
Layer quantity	360 EUR, 480 UK
Layer quantity EUR	360
Layer quantity UK	480
Pallet quantity EUR (PC)	3600
Pallet quantity UK (PC)	4800
Outer case size	590 x 120 x 102 (mm)
Product status	Available


Technical drawing




Lumen maintenance data



Survival data



Service life data



Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Linear Fluorescent Lamps Catalogue \(PDF\)](#)

[LFL T5 LongLast™ Lamps - Data sheet \(EN\) \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[LFL Lamps Spectrum Catalogue \(EN\) \(PDF\)](#)

[LFL T5 LongLast™ Lamps - Data sheet \(EN\) \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Lumen maintenance may vary for lamps with colour temperature $\geq 5000\text{K}$

